

## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: SPOT  
Beam: 36°  
Colour: WHITE  
Dimming: WITH ACCESSORY  
Emergency: WITH ACCESSORY  
A: Ø50mm  
H: 85mm  
D: 45mm  
Warranty: 5 years  
Weight: 0.17kg

## Tech data

Luminaire luminous flux: 540lm  
Luminous flux in emergency: 95%  
IP: 20  
Insulation class: III  
Supply voltage: DC 350 mA  
SELV: No

## Source

Light source: LED  
Source power: 7W  
Source luminous flux: 662lm  
Colour temperature: 3000K  
CRI: >90  
LED lifespan: 30000h L70 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2


## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 11th Oct 2017.


[View more product info](#)

## ELECTRICAL ACCESSORIES




ALIM. LED MAX 10W 350MA

**103606.99**



ALIM. LED MAX 10W 350MA DALI PUSH


**101315.99**



ALIM. LED MAX 15W 350MA

**101310.99**


## DIMMABLE ACCESSORIES



ALIM. MAX.16W/350MA DALI/PUSH/0-10/1-10


**103605.99**

## EMERGENCY ACCESSORIES



KIT EMERGENZA 1H 9V-58V

**18002.99**



KIT EMERGENZA 3H 9V-58V

**18003.99**