

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: SPOT
Beam: 36°
Colour: BLACK
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
A: Ø50mm
H: 85mm
D: 45mm
Warranty: 5 years
Weight: 0.17kg

Tech data

Luminaire luminous flux: 568lm
Luminous flux in emergency: 95%
IP: 20
Insulation class: III
Supply voltage: DC 350 mA
UGR: <19
SELV: No

Source

Light source: LED
Source power: 7W
Source luminous flux: 662lm
Colour temperature: 3000K
CRI: >90
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2


Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 11th Oct 2017.


[View more product info](#)

ELECTRICAL ACCESSORIES




ALIM. LED MAX 10W 350MA

103606.99



ALIM. LED MAX 10W 350MA DALI PUSH


101315.99



ALIM. LED MAX 15W 350MA

101310.99


DIMMABLE ACCESSORIES



ALIM. MAX.16W/350MA DALI/PUSH/0-10/1-10


103605.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 1H 9V-58V

18002.99



KIT EMERGENZA 3H 9V-58V

18003.99