

Features

Use: Indoor
Type of installation: RECESSED INTO BRICKWORK, RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: TRANSPARENT
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: 37mm
A: 37mm
H: 34mm
D: 32-35mm
Warranty: 5 years
Weight: 0.12kg

Tech data

Luminaire luminous flux: 110lm
IP: 65
Insulation class: III
Supply voltage: DC 700 MA

Source

Light source: LED
Source power: 2W
Colour temperature: 3000K
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)


MOUNTING ACCESSORIES



NEWSTEP: PLACCA MURALE


109405.99

ELECTRICAL ACCESSORIES




ALIM. LED 700MA - 30W - IP20

E907K0030KK




ALIM. LED 350MA - 8W - IP20

E903K0006KK




ALIM. LED 700MA - 12W - IP20

E907K0012KK



ALIM. LED 350MA - 15W - IP20

E903K0015KK



ALIM. LED 4W/700MA 2.5-6V

101322.99