




GIMBLE OUT

inground fitting, LED, 3000K, stainless steel 316, 36°, IP67

The GIMBLE OUT 150 LED inground fitting with round bezel and transparent glass cover is equipped with an LED module. The head of the luminaire, which also contains the LED module, can be pulled out of the luminaire by 90°. With its IP67 protection class, the luminaire is suitable for outdoor use. The electrical connection is made directly to the 230V mains supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	1000384
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	600mA
Height	13.1 cm
Diameter	18 cm
Installation diameter	15 cm
Installation depth	17 cm
Net weight	3.08 kg
Gross weight	3.281 kg
IP Code	IP 65 / IP 67
Safety class	I
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground, Ground with Acc.
Wattage	13 W
Lumen	1100 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
CRI	80
LXXBXX data	L70B50
Minimum ambient temperature	-20 °C

Light Source

916450	
--------	---

Accessories

1000655	Inground mounting pot , black for DASAR® PRE- MIUM and GIMBLE OUT
228730	CONNECTION BOX , 3-pin, IP68
233792	Inground mounting pot , with cover for DASAR PREMIUM and GIMBLE OUT DN160

Maximum ambient temperature	40 °C
Mechanical loading	0 t
BIG WHITE Page	724