



KAMUELA


fire protection recessed ceiling light, LED, 4000K, black, 38°, dimmable, IP65

The KAMUEL ECO LED recessed fitting is equipped with an integrated premium LED. The recessed light is made of aluminium and plastic and is fitted with a cold-white LED. The fire-resistant recessed fitting series is fire-resistant for at least 90 minutes. An appropriate dimmable constant current driver is integrated for operating the recessed fitting, and is therefore suitable for direct connection to 230 Volts. This luminaire contains built-in LED lamps and is available with different housing colours.

TECHNICAL DATA

Item no.:	1001017
Primary nominal voltage	220-240V ~50Hz mA/V
Height	7.1 cm
Diameter	8.8 cm
Installation diameter	7 cm
Installation depth	7.1 cm
Net weight	0.258 kg
Gross weight	0.305 kg
IP Code	IP 65
Safety class	II
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Wattage	6 W
Lumen	530 lm
Colour temperature	4000 Kelvin
Beam angle	38 °
Color	black
CRI	84

Light Source

916373		LXXBXX data	L70B50
		Minimum ambient temperature	-20 °C
		Maximum ambient temperature	40 °C
		BIG WHITE Page	710