




DOLIX OUT QPAR51

round, silver-grey

The DOLIX OUT high-voltage recessed ceiling ring is made from aluminium and has glass protection against splashing water. Thanks to its IP44 rating, it is suitable for use outdoors and in wet rooms. The integrated GU10 high-voltage fitting means the DOLIX OUT recessed ceiling ring is ready for immediate connection to the 230V mains voltage.



TECHNICAL DATA

| | |
|-------------------------|------------------------|
| Item no.: | 1001167 |
| Socket | GU10 |
| Lamp | QPAR51 |
| Number of sockets | 1 |
| Lamps included | No |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Height | 11 cm |
| Diameter | 8.2 cm |
| Installation diameter | 6.8 cm |
| Installation depth | 11 cm |
| Net weight | 0.18 kg |
| Gross weight | 0.216 kg |
| IP Code | IP 65 |
| Safety class | II |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 50 W |
| Color | grey |
| BIG WHITE Page | 713 |

Recommended lamp

| | |
|---------|--|
| 1004972 | LED QPAR51 , lightbulb GU10 2700K 36° |
| 1005075 | LED lightbulb QPAR51 , GU10, 2700K, grey |
| 1005078 | LED lightbulb QPAR51 , GU10, 3000K, grey |
| 1005273 | QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36° |