




DOLIX OUT QPAR51

square, matt chrome

The DOLIX low-voltage recessed ceiling ring is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. To operate the recessed fitting, a matching transformer for low-voltage halogen lamps is required.



TECHNICAL DATA

Item no.:	1001172
Socket	GU10
Lamp	QPAR51
Number of sockets	1
Lamps included	No
Primary nominal voltage	220-240V ~50/60Hz mA/V
Length	8.8 cm
Width	8.8 cm
Height	11 cm
Installation diameter	6.8 cm
Installation depth	11 cm
Net weight	0.197 kg
Gross weight	0.23 kg
IP Code	IP 65
Safety class	II
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	50 W
Color	silver
BIG WHITE Page	713

Recommended lamp

1004972	LED QPAR51 , lightbulb GU10 2700K 36°
1004973	LED QPAR51 , lightbulb GU10 300K 36°
1005076	LED lightbulb QPAR51 , GU10, 2700K, white
1005079	LED lightbulb QPAR51 , GU10, 3000K, white