




PANEL

1200x300mm LED Indoor surface-mounted ceiling light, 4000K, white


The LED PANEL, which is available in several different light and housing colours, provides a modern and space-saving solution for an efficient form of basic lighting. With its high lumen output and a UGR value of less than 19, it provides a pleasant, homogeneous and glare-free lighting atmosphere, even for workstations. The electrical connection is made directly to the 230V mains voltage supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1001506 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 1000mA |
| Length | 119.5 cm |
| Width | 29.5 cm |
| Height | 5 cm |
| Net weight | 4.445 kg |
| Gross weight | 5.312 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Number of through-wires | 40 |
| Wattage | 45 W |
| Lumen | 3400 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 90 ° |
| Color | white |
| CRI | 80 |
| UGR ≤ | 19 |

Light Source

| | | | |
|--------|---|----------------|--------|
| 916385 |  | LXXBXX data | L70B50 |
| | | BIG WHITE Page | 262 |