




## MEDO 40 EL

LED indoor recessed ceiling light, frameless version, white, 3000/4000K

The recessed version of the MEDO series fits into every room concept seamlessly thanks to its understated design. The MEDO Frameless combines with the ceiling in a charming way. The light colour can be easily switched between 3000K and 4000K prior to installation using a switch. The integrated premium LED module provides an even lighting effect. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



## **TECHNICAL DATA**

Item no.:	1001902
Secondary power / secondary volta- ge	700mA
Height	9.5 cm
Diameter	38 cm
Installation diameter	39 cm
Installation depth	13 cm
Net weight	2.016 kg
Gross weight	2.917 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	28 W
Lumen	3300 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	white
CRI	80
UGR≤	25
LXXBXX data	L70B50
Maximum ambient temperature	40 °C
BIG WHITE Page	415



## **Light Source**

916346	A C
Accessories	
1002424	LED driver MEDO 400 , dimmable DALI/1-10V
1005446	LED driver , 40W 700mA PHASE
1006120	LED driver , 40W 700/900/1000mA