






## **FLATT**

## Outdoor LED surface-mounted wall light 3000K IP65 anthracite/brown

Would you like a wall light which can be fitted effortlessly? This should have a safety class of at least IP 65, and therefore be thus dustproof and protected from water spray from various directions. Our FLATT WL has IP 65 and is suitable for providing a surface, path or terrace with fantastic illumination. Are you looking for amazing light for your outdoor area? This is provided by the built-in Premium LED of the FLATT POLE 65 floor stand. Incidentally, the FLATT POLE 65 gives you even more advantages as a part of the SLV family. Because we have been successful with our lighting concepts for 40 years, and keep setting the bar higher for ourselves and our products.




## **TECHNICAL DATA**

Primary nominal voltage 100-277V ~50/60Hz mA/V  Secondary power / secondary voltage 300mA  Width 18 cm  Height 23 cm  Depth 7 cm  Net weight 2.013 kg  Gross weight 2.284 kg  IP Code IP 65  Safety class I  Impact resistance class IK03  Impact resistance 0,35 Joule  Assembly Surface	
ge         Width         18 cm           Height         23 cm           Depth         7 cm           Net weight         2.013 kg           Gross weight         2.284 kg           IP Code         IP 65           Safety class         I           Impact resistance class         IK03           Impact resistance         0,35 Joule	
Height   23 cm	
Depth 7 cm  Net weight 2.013 kg  Gross weight 2.284 kg  IP Code IP 65  Safety class I  Impact resistance class IK03  Impact resistance 0,35 Joule	
Net weight       2.013 kg         Gross weight       2.284 kg         IP Code       IP 65         Safety class       I         Impact resistance class       IK03         Impact resistance       0,35 Joule	
Gross weight 2.284 kg  IP Code IP 65  Safety class I  Impact resistance class IK03  Impact resistance 0,35 Joule	
IP Code IP 65  Safety class I  Impact resistance class IK03  Impact resistance 0,35 Joule	
Safety class  Impact resistance class  Impact resistance  0,35 Joule	
Impact resistance class IK03 Impact resistance 0,35 Joule	
Impact resistance 0,35 Joule	
Assembly Surface	
Assembly details Wall	
Wattage 14 W	
Lumen 500 lm	
Colour temperature 3000/4000 Kelvin	
Color brown	
<b>CRI</b> 80	
LXXBXX data L70B50	
Ambient temperature 40 °C	
Minimum ambient temperature -25 °C	



## **Light Source**



Maximum ambient temperature	40 °C
BIG WHITE Page	640