




## NOTAPO II

### Indoor recessed wall light 3000K white

Aluminium recessed wall light NOTAPO II WL. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The NOTAPO II recessed fitting is available with a white housing. An installation frame and a mounting box for installation in masonry are optionally available. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

|                                     |                      |
|-------------------------------------|----------------------|
| Item no.:                           | 1002980              |
| Secondary power / secondary voltage | 700mA                |
| Width                               | 3.6 cm               |
| Height                              | 18 cm                |
| Depth                               | 3.8 cm               |
| Installation length                 | 17.3 cm              |
| Installation width                  | 2.8 cm               |
| Installation depth                  | 5 cm                 |
| Net weight                          | 0.104 kg             |
| Gross weight                        | 0.157 kg             |
| IP Code                             | IP 20                |
| Safety class                        | III                  |
| Assembly                            | Recessed             |
| Assembly details                    | Wall, Wall with Acc. |
| Lumen                               | 6 lm                 |
| Colour temperature                  | 3000 Kelvin          |
| Color                               | white                |
| CRI                                 | 90                   |
| LXXBXX data                         | L70B50               |
| Maximum ambient temperature         | 40 °C                |
| BIG WHITE Page                      | 410                  |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 954799 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                          |
|---------|----------------------------------------------------------|
| 1002981 | NOTAPO I and II WL , installation frame                  |
| 464142  | LED DRIVER , 10.5W, 700mA, incl. strain relief, dimmable |
| 464200  | LED DRIVER , 3W, 700mA, incl. strain relief              |