





## LED PANEL 620x620

## Indoor LED recessed ceiling light white 3000K UGR<19

The LED PANEL 620 comes in several different light colours for grid ceilings and provides a modern and space-saving solution for an efficient kind of base lighting. You achieve a pleasant, homogeneous and glare-free lighting sensation with this product, with an aperture angle of less than 19°.



## **TECHNICAL DATA**

Item no.:	1003073
Secondary power / secondary voltage	1050mA
Length	61.7 cm
Width	61.7 cm
Height	0.9 cm
Installation depth	5 cm
Net weight	3.166 kg
Gross weight	4.044 kg
IP Code	IP 20
Safety class	Ш
Assembly	Recessed
Assembly details	Ceiling, Ceiling with Acc.
Lumen	4000 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	90
UGR≤	19
LXXBXX data	L70B50
BIG WHITE Page	419



## **Light Source**

916571	
Accessories	
1002425	LED driver MEDO 600 , dimmable DALI/1-10V
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PA- NEL, white
158799	SUSPENSION SET, for LED PANEL, I-VIDUAL and I-VIDUAL LED PA- NEL, steel wire and Y-wire suspension
464804	LED DRIVER , 40W, 1050mA, triac dimmable