




LED PANEL 620x620

Indoor LED recessed ceiling light white 4000K
UGR<19

The LED PANEL for grid ceilings, which can be switched between two light colours, is a modern and space saving solution for an efficient kind of basic lighting. You achieve a pleasant, homogeneous and glare-free lighting sensation with this product, with an aperture angle of less than 19°.



TECHNICAL DATA

Item no.:	1003074
Secondary power / secondary voltage	1050mA
Length	61.7 cm
Width	61.7 cm
Height	0.9 cm
Installation depth	5 cm
Net weight	3.151 kg
Gross weight	3.769 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Ceiling with Acc.
Lumen	4000 lm
Colour temperature	4000 Kelvin
Beam angle	120 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L70B50
BIG WHITE Page	419

Light Source

916349	
--------	---

Accessories

1002425	LED driver MEDO 600 , dimmable DALI/1-10V
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PA- NEL, white
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PA- NEL, steel wire and Y-wire suspension
464804	LED DRIVER , 40W, 1050mA, triac dimmable