




## GALEN 60 SP

Indoor single colour LED profile anthracite CCT switch 3000/4000K

Thanks to the integrated mounting bracket and the splash-proof connection cables, the GALEN LED profile can be installed quickly and easily on walls, floors, or ceilings. It is most suitable as a form of lighting for displays and signs. Added to this is the practical CCT switch, which provides added flexibility as it allows the light colour to be adjusted between 3000K (warm white) and 4000K (neutral white) using an external switch. Robustly made and featuring high-performance LEDs, GALEN is perfect for creating effective or functional lighting in the outdoor areas of shops, hotels, restaurants, or in commercial buildings.



### TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1003447                |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 450mA                  |
| Width                               | 60 cm                  |
| Height                              | 6.2 cm                 |
| Depth                               | 11.3 cm                |
| Net weight                          | 1.703 kg               |
| Gross weight                        | 1.849 kg               |
| IP Code                             | IP 65                  |
| Safety class                        | I                      |
| Impact resistance class             | IK03                   |
| Impact resistance                   | 0,35 Joule             |
| Assembly                            | Surface                |
| Assembly details                    | Ceiling, Ground, Wall  |
| Number of through-wires             | 12                     |
| Wattage                             | 18 W                   |
| Colour temperature                  | 3000/4000 Kelvin       |
| Color                               | anthracite             |
| CRI                                 | 80                     |
| LXXBXX data                         | L70B50                 |
| Minimum ambient temperature         | -20 °C                 |
| Maximum ambient temperature         | 45 °C                  |

## Light Source

|        |   |
|--------|---|
| 916615 |  |
|--------|---|

|                |     |
|----------------|-----|
| BIG WHITE Page | 591 |
|----------------|-----|

## Accessories

|        |   |
|--------|---|
| 231960 | CONNECTION CABLE ,<br>for GALEN outdoor wall<br>light, black, 5 m |
| 231961 | CONNECTION CABLE ,<br>for GALEN outdoor wall<br>light, black, 1 m |