






## L-LINE OUT WL

## Outdoor LED wall-mounted light anthracite CCT switch 3000/4000K

With its linear light variety, the L-LINE OUT family lights the way outdoors. Despite their individual differences, the individual members speak a common language of form, encapsulated in the clean lines of the letter "L". As far as lighting technology is concerned, there are no compromises: the CCT switch for easy selection of light colour temperature (3000 or 4000K) prior to installation), the straightforward installation process, and a protection rating of IP 65 are just some of the features that make the L-LINE OUT surface-mounted wall light a winner.



## **TECHNICAL DATA**

Item no.:	1003539	
Number of different light outlets	1	
Primary nominal voltage	220-240V ~50/60Hz mA/V	
Secondary power / secondary volta- ge	350mA	
Width	15 cm	
Height	10 cm	
Depth	10 cm	
Net weight	1.024 kg	
Gross weight	1.237 kg	
IP Code	IP 65	
Safety class	1	
Impact resistance class	IK02	
Impact resistance	0,2 Joule	
Assembly	Surface	
Assembly details	Wall	
Number of through-wires	10	
Wattage	7 W	
Lumen	570 lm	
Colour temperature	3000/4000 Kelvin	
Color	anthracite	
CRI	80	
LXXBXX data	L70B50	



## Light Source

916406	Î C	Minimum ambient temperature	-20 °C
		Maximum ambient temperature	45 °C
		BIG WHITE Page	656