



NUMINOS® MOVE DL M

**Indoor LED recessed ceiling light black/black 2700K
55° rotating and pivoting**

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® MOVE DL M recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 17.55 watts, luminous flux of 1460 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.:	1003559
Number of different light outlets	1
Secondary power / secondary voltage	500mA
Height	9 cm
Diameter	13.5 cm
Installation diameter	12 cm
Installation depth	10 cm
Net weight	0.39 kg
Gross weight	0.45 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	17.55 W
Lumen	1460 lm
Colour temperature	2700 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR ≤	22

Light Source

791800	
--------	---

Accessories

1004054	LED driver , 20W 500mA PHASE
1004064	LED driver , 21-29.5W 500/600/700mA
1004069	LED driver , 29W 500mA
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma
1004792	NUMINOS® M , diffuser Frosted
1004793	NUMINOS® M , diffuser Wabe
1006143	Numinos® M Mounting Frame , round 240/120mm black
1006144	Numinos® M Mounting Frame , round 240/120mm white
1006145	Numinos® M Mounting Frame , square 240/120mm black
1006146	Numinos® M Mounting Frame , square 240/120mm white

LXXBXX data	L80B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	42