




## NUMINOS® MOVE DL M

Indoor LED recessed ceiling light white/black 2700K  
20° rotating and pivoting

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of down-lights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® MOVE DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 17.55 watts, luminous flux of 1460 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



## TECHNICAL DATA

|                                     |             |
|-------------------------------------|-------------|
| Item no.:                           | 1003565     |
| Number of different light outlets   | 1           |
| Secondary power / secondary voltage | 500mA       |
| Height                              | 9 cm        |
| Diameter                            | 13.5 cm     |
| Installation diameter               | 12 cm       |
| Installation depth                  | 10 cm       |
| Net weight                          | 0.355 kg    |
| Gross weight                        | 0.38 kg     |
| IP Code                             | IP 20       |
| Safety class                        | III         |
| Impact resistance class             | IK02        |
| Impact resistance                   | 0,2 Joule   |
| Assembly                            | Recessed    |
| Assembly details                    | Ceiling     |
| Wattage                             | 17.55 W     |
| Lumen                               | 1460 lm     |
| Colour temperature                  | 2700 Kelvin |
| Beam angle                          | 20 °        |
| Color                               | white       |
| CRI                                 | 90          |
| UGR ≤                               | 19          |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791800 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                    |
|---------|----------------------------------------------------|
| 1004054 | LED driver , 20W 500mA PHASE                       |
| 1004064 | LED driver , 21-29.5W 500/600/700mA                |
| 1004069 | LED driver , 29W 500mA                             |
| 1004790 | NUMINOS® M , diffuser Ellipse                      |
| 1004791 | NUMINOS® M , diffuser Prisma                       |
| 1004792 | NUMINOS® M , diffuser Frosted                      |
| 1004793 | NUMINOS® M , diffuser Wabe                         |
| 1006143 | Numinos® M Mounting Frame , round 240/120mm black  |
| 1006144 | Numinos® M Mounting Frame , round 240/120mm white  |
| 1006145 | Numinos® M Mounting Frame , square 240/120mm black |
| 1006146 | Numinos® M Mounting Frame , square 240/120mm white |

|                             |        |
|-----------------------------|--------|
| LXXBXX data                 | L80B50 |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C  |
| BIG WHITE Page              | 42     |