




## NUMINOS® MOVE DL M

Indoor LED recessed ceiling light white/chrome 4000K  
55° rotating and pivoting

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® MOVE DL M, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 17.55 watts, luminous flux of 1660 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                     |             |
|-------------------------------------|-------------|
| Item no.:                           | 1003621     |
| Number of different light outlets   | 1           |
| Secondary power / secondary voltage | 500mA       |
| Height                              | 9 cm        |
| Diameter                            | 13.5 cm     |
| Installation diameter               | 12 cm       |
| Installation depth                  | 10 cm       |
| Net weight                          | 0.39 kg     |
| Gross weight                        | 0.45 kg     |
| IP Code                             | IP 20       |
| Safety class                        | III         |
| Impact resistance class             | IK02        |
| Impact resistance                   | 0,2 Joule   |
| Assembly                            | Recessed    |
| Assembly details                    | Ceiling     |
| Wattage                             | 17.55 W     |
| Lumen                               | 1660 lm     |
| Colour temperature                  | 4000 Kelvin |
| Beam angle                          | 55 °        |
| Color                               | white       |
| CRI                                 | 90          |
| UGR ≤                               | 19          |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791825 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                          |
|---------|----------------------------------------------------------|
| 1004054 | LED driver , 20W 500mA<br>PHASE                          |
| 1004064 | LED driver , 21-29.5W<br>500/600/700mA                   |
| 1004069 | LED driver , 29W 500mA                                   |
| 1004790 | NUMINOS® M , diffuser<br>Ellipse                         |
| 1004791 | NUMINOS® M , diffuser<br>Prisma                          |
| 1004792 | NUMINOS® M , diffuser<br>Frosted                         |
| 1004793 | NUMINOS® M , diffuser<br>Wabe                            |
| 1006143 | Numinos® M Mounting<br>Frame , round<br>240/120mm black  |
| 1006144 | Numinos® M Mounting<br>Frame , round<br>240/120mm white  |
| 1006145 | Numinos® M Mounting<br>Frame , square<br>240/120mm black |
| 1006146 | Numinos® M Mounting<br>Frame , square<br>240/120mm white |

|                             |        |
|-----------------------------|--------|
| LXXBXX data                 | L80B50 |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C  |
| BIG WHITE Page              | 42     |