




NUMINOS® MOVE DL L

Indoor LED recessed ceiling light white/white 3000K 20° rotating and pivoting

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® MOVE DL L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 25.41 watts, a luminous flux of 2300 lumens, a colour temperature of 3000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.:	1003662
Number of different light outlets	1
Secondary power / secondary voltage	700mA
Height	9.5 cm
Diameter	16 cm
Installation diameter	14.5 cm
Installation depth	10.5 cm
Net weight	0.54 kg
Gross weight	0.68 kg
IP Code	IP 20
Safety class	Ш
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	25.41 W
Lumen	2300 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR≤	19



Light Source

791822	Ĉ E	
Accessories		
1004062	LED driver , 21-29.5W 500/600/700mA	
1004065	LED driver , 30W 700mA	
1004070	LED driver , 40W 700mA	
1004794	NUMINOS® L , diffuser Ellipse	
1004795	NUMINOS® L , diffuser Prisma	
1004796	NUMINOS® L , diffuser Frosted	
1004797	NUMINOS® L , diffuser Wabe	
1006147	Numinos® L Mounting Frame , round 240/150mm black	
1006148	Numinos® L Mounting Frame , round 240/150mm white	
1006149	Numinos® L Mounting Frame , square 240/150mm black	
1006150	Numinos® L Mounting Frame , square 240/150mm white	

LXXBXX data	L80B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	44