




## NUMINOS® MOVE DL L

Indoor LED recessed ceiling light black/black 4000K  
40° rotating and pivoting

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® MOVE DL L recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 25.41 watts, luminous flux of 2350 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.:	1003673
Number of different light outlets	1
Secondary power / secondary voltage	700mA
Height	9.5 cm
Diameter	16 cm
Installation diameter	14.5 cm
Installation depth	10.5 cm
Net weight	0.54 kg
Gross weight	0.68 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	25.41 W
Lumen	2350 lm
Colour temperature	4000 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	22

## Light Source

791825	
--------	---

## Accessories

1004062	LED driver , 21-29.5W 500/600/700mA
1004065	LED driver , 30W 700mA
1004070	LED driver , 40W 700mA
1004794	NUMINOS® L , diffuser Ellipse
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1004797	NUMINOS® L , diffuser Wabe
1006147	Numinos® L Mounting Frame , round 240/150mm black
1006148	Numinos® L Mounting Frame , round 240/150mm white
1006149	Numinos® L Mounting Frame , square 240/150mm black
1006150	Numinos® L Mounting Frame , square 240/150mm white

LXXBXX data	L80B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	44