




NUMINOS® MOVE DL L

Indoor LED recessed ceiling light white/chrome 4000K
20° rotating and pivoting

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The different downlights and spotlights make a thousand lighting design options possible. Like with the NUMINOS® MOVE DL L recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2350 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| | |
|-------------------------------------|-------------|
| Item no.: | 1003687 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 700mA |
| Height | 9.5 cm |
| Diameter | 16 cm |
| Installation diameter | 14.5 cm |
| Installation depth | 10.5 cm |
| Net weight | 0.54 kg |
| Gross weight | 0.68 kg |
| IP Code | IP 20 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 25.41 W |
| Lumen | 2350 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 20 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 19 |

Light Source

| | |
|--------|---|
| 791825 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1004062 | LED driver , 21-29.5W 500/600/700mA |
| 1004065 | LED driver , 30W 700mA |
| 1004070 | LED driver , 40W 700mA |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1004797 | NUMINOS® L , diffuser Wabe |
| 1006147 | Numinos® L Mounting Frame , round 240/150mm black |
| 1006148 | Numinos® L Mounting Frame , round 240/150mm white |
| 1006149 | Numinos® L Mounting Frame , square 240/150mm black |
| 1006150 | Numinos® L Mounting Frame , square 240/150mm white |

| | |
|-----------------------------|--------|
| LXXBXX data | L80B50 |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 44 |