




NUMINOS® MOVE DL XL

Indoor LED recessed ceiling light white/white 2700K
55° rotating and pivoting

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® MOVE DL XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 37.4 watts, a luminous flux of 3500 lumens, a colour temperature of 2700 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.:	1003716
Number of different light outlets	1
Secondary power / secondary voltage	1050mA
Height	11.8 cm
Diameter	19 cm
Installation diameter	17.5 cm
Installation depth	13 cm
Net weight	0.7 kg
Gross weight	0.89 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	37.4 W
Lumen	3500 lm
Colour temperature	2700 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR ≤	19

Light Source

791857	
--------	---

Accessories

1004059	LED driverm 40W multi mA
1004066	LED driver , 28-40W 1000mA PHASE
1004071	LED driver 4.2-50W 1050mA DALI
1004798	NUMINOS® XL , diffuser Ellipse
1004799	NUMINOS® XL , diffuser Prisma
1004800	NUMINOS® XL , diffuser Frosted
1004801	NUMINOS® XL , diffuser Wabe
1006151	Numinos® XL Mounting Frame , round 240/180mm black
1006152	Numinos® XL Mounting Frame , round 240/180mm white
1006153	Numinos® XL Mounting Frame , square 240/180mm black
1006154	Numinos® XL Mounting Frame , square 240/180mm white

LXXBXX data	L80B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	46