




NUMINOS® MOVE DL XL

Indoor LED recessed ceiling light white/chrome 3000K
20° rotating and pivoting

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® MOVE DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 37.4 watts, a luminous flux of 3500 lumens, a colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.:	1003735
Number of different light outlets	1
Secondary power / secondary voltage	1050mA
Height	11.8 cm
Diameter	19 cm
Installation diameter	17.5 cm
Installation depth	13 cm
Net weight	0.66 kg
Gross weight	0.706 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	37.4 W
Lumen	3500 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	19

Light Source

791823	
--------	---

Accessories

1004059	LED driverm 40W multi mA
1004066	LED driver , 28-40W 1000mA PHASE
1004071	LED driver 4.2-50W 1050mA DALI
1004798	NUMINOS® XL , diffuser Ellipse
1004799	NUMINOS® XL , diffuser Prisma
1004800	NUMINOS® XL , diffuser Frosted
1004801	NUMINOS® XL , diffuser Wabe
1006151	Numinos® XL Mounting Frame , round 240/180mm black
1006152	Numinos® XL Mounting Frame , round 240/180mm white
1006153	Numinos® XL Mounting Frame , square 240/180mm black
1006154	Numinos® XL Mounting Frame , square 240/180mm white

LXXBXX data	L80B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	46