




## NUMINOS® DL S

Indoor LED recessed ceiling light white/black 3000K  
20° gimballed, rotating and pivoting, including leaf  
springs

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® DL S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 8.6 watts, luminous flux of 690 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



## TECHNICAL DATA

Item no.:	1003805
Number of different light outlets	1
Secondary power / secondary voltage	250mA
Height	5.2 cm
Diameter	8 cm
Installation diameter	6.8 cm
Installation depth	5.5 cm
Net weight	0.16 kg
Gross weight	0.2 kg
IP Code	IP 20 / IP 44
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	8.6 W
Lumen	690 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	19

## Light Source

791815	
--------	---

## Accessories

1004055	LED driver , 6.5-10W 250mA PHASE
1004058	LED driver , 6.5-10W 250mA
1004067	LED driver , 15W 250mA DALI
1004786	NUMINOS® S , diffuser Ellipse
1004787	NUMINOS® S , diffuser Prisma
1004788	NUMINOS® S , diffuser Frosted
1004789	NUMINOS® S , diffuser Wabe
1006135	Numinos® XS Mounting Frame , round 160/70mm black
1006136	Numinos® XS Mounting Frame , round 160/70mm white
1006137	Numinos® XS Mounting Frame , square 160/70mm black
1006138	Numinos® XS Mounting Frame , square 160/70mm white

LXXBXX data	L80B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	31