




## NUMINOS® DL M

Indoor LED recessed ceiling light white/white 2700K 40°, including leaf springs

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® DL M recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 17.55 watts, luminous flux of 1600 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                     |               |
|-------------------------------------|---------------|
| Item no.:                           | 1003857       |
| Number of different light outlets   | 1             |
| Secondary power / secondary voltage | 500mA         |
| Height                              | 6.8 cm        |
| Diameter                            | 10.5 cm       |
| Installation diameter               | 9 cm          |
| Installation depth                  | 7.5 cm        |
| Net weight                          | 0.24 kg       |
| Gross weight                        | 0.28 kg       |
| IP Code                             | IP 20 / IP 44 |
| Safety class                        | III           |
| Impact resistance class             | IK02          |
| Impact resistance                   | 0,2 Joule     |
| Assembly                            | Recessed      |
| Assembly details                    | Ceiling       |
| Wattage                             | 17.55 W       |
| Lumen                               | 1600 lm       |
| Colour temperature                  | 2700 Kelvin   |
| Beam angle                          | 40 °          |
| Color                               | white         |
| CRI                                 | 90            |
| UGR ≤                               | 19            |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791800 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                          |
|---------|----------------------------------------------------------|
| 1004054 | LED driver , 20W 500mA<br>PHASE                          |
| 1004064 | LED driver , 21-29.5W<br>500/600/700mA                   |
| 1004069 | LED driver , 29W 500mA                                   |
| 1004790 | NUMINOS® M , diffuser<br>Ellipse                         |
| 1004791 | NUMINOS® M , diffuser<br>Prisma                          |
| 1004792 | NUMINOS® M , diffuser<br>Frosted                         |
| 1004793 | NUMINOS® M , diffuser<br>Wabe                            |
| 1006139 | Numinos® S Mounting<br>Frame , round<br>160/100mm black  |
| 1006140 | Numinos® S Mounting<br>Frame , round<br>160/100mm white  |
| 1006141 | Numinos® S Mounting<br>Frame , square<br>160/100mm black |
| 1006142 | Numinos® S Mounting<br>Frame , square<br>160/100mm white |

|                             |        |
|-----------------------------|--------|
| LXXBXX data                 | L80B50 |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C  |
| BIG WHITE Page              | 32     |