




NUMINOS® DL M

Indoor LED recessed ceiling light white/white 4000K 40°, including leaf springs

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL M recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 17.55 watts, luminous flux of 1750 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|-------------------------------------|---------------|
| Item no.: | 1003905 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 500mA |
| Height | 6.8 cm |
| Diameter | 10.5 cm |
| Installation diameter | 9 cm |
| Installation depth | 7.5 cm |
| Net weight | 0.24 kg |
| Gross weight | 0.28 kg |
| IP Code | IP 20 / IP 44 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 17.55 W |
| Lumen | 1750 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 40 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |

Light Source

| | |
|--------|---|
| 791825 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1004054 | LED driver , 20W 500mA PHASE |
| 1004064 | LED driver , 21-29.5W 500/600/700mA |
| 1004069 | LED driver , 29W 500mA |
| 1004790 | NUMINOS® M , diffuser Ellipse |
| 1004791 | NUMINOS® M , diffuser Prisma |
| 1004792 | NUMINOS® M , diffuser Frosted |
| 1004793 | NUMINOS® M , diffuser Wabe |
| 1006139 | Numinos® S Mounting Frame , round 160/100mm black |
| 1006140 | Numinos® S Mounting Frame , round 160/100mm white |
| 1006141 | Numinos® S Mounting Frame , square 160/100mm black |
| 1006142 | Numinos® S Mounting Frame , square 160/100mm white |

| | |
|-----------------------------|--------|
| LXXBXX data | L80B50 |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 32 |