




## NUMINOS® DL L

Indoor LED recessed ceiling light white/white 2700K 20°

The NUMINOS light system from SLV skilfully combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 25.41 watts, a luminous flux of 2250 lumens, a colour temperature of 2700 Kelvin and a good colour reproduction index of over 90. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

Item no.:	1003926
Number of different light outlets	1
Secondary power / secondary voltage	700mA
Height	8.5 cm
Diameter	13 cm
Installation diameter	11.7 cm
Installation depth	9 cm
Net weight	0.465 kg
Gross weight	0.525 kg
IP Code	IP 20 / IP 44
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	25.41 W
Lumen	2250 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	19

## Light Source

791800	
--------	---

## Accessories

1004062	LED driver , 21-29.5W 500/600/700mA
1004065	LED driver , 30W 700mA
1004070	LED driver , 40W 700mA
1004794	NUMINOS® L , diffuser Ellipse
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1004797	NUMINOS® L , diffuser Wabe
1006143	Numinos® M Mounting Frame , round 240/120mm black
1006144	Numinos® M Mounting Frame , round 240/120mm white
1006145	Numinos® M Mounting Frame , square 240/120mm black
1006146	Numinos® M Mounting Frame , square 240/120mm white

LXXBXX data	L80B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	34