




NUMINOS® DL L

Indoor LED recessed ceiling light white/white 3000K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2300 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| | |
|-------------------------------------|---------------|
| Item no.: | 1003956 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 700mA |
| Height | 8.5 cm |
| Diameter | 13 cm |
| Installation diameter | 11.7 cm |
| Installation depth | 9 cm |
| Net weight | 0.465 kg |
| Gross weight | 0.525 kg |
| IP Code | IP 20 / IP 44 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 25.41 W |
| Lumen | 2300 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |

Light Source

| | |
|--------|---|
| 791822 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1004062 | LED driver , 21-29.5W 500/600/700mA |
| 1004065 | LED driver , 30W 700mA |
| 1004070 | LED driver , 40W 700mA |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1004797 | NUMINOS® L , diffuser Wabe |
| 1006143 | Numinos® M Mounting Frame , round 240/120mm black |
| 1006144 | Numinos® M Mounting Frame , round 240/120mm white |
| 1006145 | Numinos® M Mounting Frame , square 240/120mm black |
| 1006146 | Numinos® M Mounting Frame , square 240/120mm white |

| | |
|-----------------------------|--------|
| LXXBXX data | L80B50 |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 34 |