




## NUMINOS® DL L

Indoor LED recessed ceiling light black/chrome 4000K 55°

The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® DL L recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2350 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

|                                     |               |
|-------------------------------------|---------------|
| Item no.:                           | 1003969       |
| Number of different light outlets   | 1             |
| Secondary power / secondary voltage | 700mA         |
| Height                              | 8.5 cm        |
| Diameter                            | 13 cm         |
| Installation diameter               | 11.7 cm       |
| Installation depth                  | 9 cm          |
| Net weight                          | 0.465 kg      |
| Gross weight                        | 0.525 kg      |
| IP Code                             | IP 20 / IP 44 |
| Safety class                        | III           |
| Impact resistance class             | IK02          |
| Impact resistance                   | 0,2 Joule     |
| Assembly                            | Recessed      |
| Assembly details                    | Ceiling       |
| Wattage                             | 25.41 W       |
| Lumen                               | 2350 lm       |
| Colour temperature                  | 4000 Kelvin   |
| Beam angle                          | 55 °          |
| Color                               | black         |
| CRI                                 | 90            |
| UGR ≤                               | 19            |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791825 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                          |
|---------|----------------------------------------------------------|
| 1004062 | LED driver , 21-29.5W<br>500/600/700mA                   |
| 1004065 | LED driver , 30W 700mA                                   |
| 1004070 | LED driver , 40W 700mA                                   |
| 1004794 | NUMINOS® L , diffuser<br>Ellipse                         |
| 1004795 | NUMINOS® L , diffuser<br>Prisma                          |
| 1004796 | NUMINOS® L , diffuser<br>Frosted                         |
| 1004797 | NUMINOS® L , diffuser<br>Wabe                            |
| 1006143 | Numinos® M Mounting<br>Frame , round<br>240/120mm black  |
| 1006144 | Numinos® M Mounting<br>Frame , round<br>240/120mm white  |
| 1006145 | Numinos® M Mounting<br>Frame , square<br>240/120mm black |
| 1006146 | Numinos® M Mounting<br>Frame , square<br>240/120mm white |

|                             |        |
|-----------------------------|--------|
| LXXBXX data                 | L80B50 |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C  |
| BIG WHITE Page              | 34     |