




NUMINOS® DL XL

Indoor LED recessed ceiling light white/white 4000K 20°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 37.4 watts, luminous flux of 3800 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.:	1004046
Number of different light outlets	1
Secondary power / secondary volta- ge	1050mA
Height	10.8 cm
Diameter	16 cm
Installation diameter	14.5 cm
Installation depth	11.5 cm
Net weight	0.715 kg
Gross weight	0.87 kg
IP Code	IP 20 / IP 44
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	37.4 W
Lumen	3800 lm
Colour temperature	4000 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR≤	19
	,



Light Source

791850	A E
Accessories	
1004059	LED driverm 40W multi mA
1004066	LED driver , 28-40W 1000mA PHASE
1004071	LED driver 4.2-50W 1050mA DALI
1004798	NUMINOS® XL , diffuser Ellipse
1004799	NUMINOS® XL , diffuser Prisma
1004800	NUMINOS® XL , diffuser Frosted
1004801	NUMINOS® XL , diffuser Wabe
1006147	Numinos® L Mounting Frame , round 240/150mm black

LXXBXX data	L80B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	36