




## 3~ NUMINOS® PHASE S

### 3 phase system light black/black 2700K 60°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the 3~ NUMINOS® PHASE S 3-phase system light LED, which convinces with best workmanship and light quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 980 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.:	1004076
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	250mA
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.5 kg
Gross weight	0.8 kg
Safety class	I
Assembly details	Track Ceiling, Track Wall
Dimmable	Yes
Dimming technology	trailing edge
Wattage	10.42 W
Lumen	980 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50
BIG WHITE Page	62

## Light Source

791819	 An energy label icon consisting of a yellow arrow pointing right, with the letters 'A' and 'G' stacked vertically inside it.
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------