




## 3~ NUMINOS® PHASE S

## 3 phase system light whitek/black 4000K $60^{\circ}$

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the 3~ NUMI-NOS® PHASE S 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1100 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



## **TECHNICAL DATA**

Item no.:	1004096
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	250mA
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.5 kg
Gross weight	0.8 kg
Safety class	I
Assembly details	Track Ceiling, Track Wall
Dimmable	Yes
Dimming technology	trailing edge
Wattage	10.42 W
Lumen	1100 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR≤	19
LXXBXX data	L80B50
BIG WHITE Page	62



## **Light Source**

791831	
Accessories	
1006167	NUMINOS® S , white front ring