




NUMINOS® DL S

**Indoor LED recessed ceiling light black/black 2700K
24° gimballed, rotating and pivoting**

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® SPOT PHASE S indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 985 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1004098 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 250mA |
| Length | 16.2 cm |
| Height | 14.5 cm |
| Diameter | 6.5 cm |
| Net weight | 0.58 kg |
| Gross weight | 0.87 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling, Wall |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Wattage | 10.42 W |
| Lumen | 985 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 24 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 16 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 72 |

Light Source

| | |
|--------|---|
| 791819 |  |
|--------|---|

Accessories

| | |
|---------|----------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|----------------------------------|