






NUMINOS® SPOT PHA-SES

Indoor LED recessed ceiling light white/black 3000K 60°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® SPOT PHASE S indoor ceiling-mounted light LED, which impresses with its high-quality work-manship and light. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1020 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Primary nominal voltage Secondary power / secondary voltage Length 16.2 cm Height 14.5 cm Diameter 6.5 cm Net weight 0.58 kg Gross weight Safety class I Assembly Assembly Assembly details Dimmable Dimming technology 220-240V ~50/60Hz mA/V 250mA 250mA 250mA 16.2 cm 10.2 cm 10.3 kg 10.5 kg Celling, Wall Yes Dimming technology	Item no.:	1004112
ge 16.2 cm Height 14.5 cm Diameter 6.5 cm Net weight 0.58 kg Gross weight 0.87 kg Safety class I Assembly Surface Assembly details Ceiling,Wall Dimmable Yes	Primary nominal voltage	220-240V ~50/60Hz mA/V
Height 14.5 cm Diameter 6.5 cm Net weight 0.58 kg Gross weight 0.87 kg Safety class I Assembly Surface Assembly details Ceiling, Wall Dimmable Yes	Secondary power / secondary volta- ge	250mA
Diameter 6.5 cm Net weight 0.58 kg Gross weight 0.87 kg Safety class I Assembly Surface Assembly details Ceiling, Wall Dimmable Yes	Length	16.2 cm
Net weight 0.58 kg Gross weight 0.87 kg Safety class I Assembly Surface Assembly details Ceiling,Wall Dimmable Yes	Height	14.5 cm
Gross weight O.87 kg Safety class I Assembly Surface Assembly details Ceiling,Wall Dimmable Yes	Diameter	6.5 cm
Safety class Assembly Surface Assembly details Ceiling, Wall Dimmable Yes	Net weight	0.58 kg
Assembly Surface Assembly details Ceiling,Wall Dimmable Yes	Gross weight	0.87 kg
Assembly details Ceiling, Wall Dimmable Yes	Safety class	I
Dimmable Yes	Assembly	Surface
	Assembly details	Ceiling, Wall
Dimming technology trailing edge	Dimmable	Yes
	Dimming technology	trailing edge
Wattage 10.42 W	Wattage	10.42 W
Lumen 1020 lm	Lumen	1020 lm
Colour temperature 3000 Kelvin	Colour temperature	3000 Kelvin
Beam angle 60 °	Beam angle	60 °
Color white	Color	white
CRI 90	CRI	90
UGR ≤ 19	UGR≤	19
LXXBXX data L80B50	LXXBXX data	L80B50
BIG WHITE Page 72	BIG WHITE Page	72



Light Source

791815	A E
Accessories	
1006169	NUMINOS® L , white front ring