




## **NUMINOS® CL PHASE S**

## Indoor LED surface ceiling light white/black 2700K $36^{\circ}$

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® CL PHASE S indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 985 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



## **TECHNICAL DATA**

Item no.:	1004127
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	250mA
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.425 kg
Gross weight	0.65 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	10.42 W
Lumen	985 lm
Colour temperature	2700 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR≤	16
LXXBXX data	L80B50
BIG WHITE Page	80



## **Light Source**

791819	â E
Accessories	
1006169	NUMINOS® L , white front ring