


NUMINOS® CL PHASE S

Indoor LED surface ceiling light black/black 4000K 60°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® CL PHASE S indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1100 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1004140 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 250mA |
| Height | 16.2 cm |
| Diameter | 6.5 cm |
| Net weight | 0.425 kg |
| Gross weight | 0.65 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Wattage | 10.42 W |
| Lumen | 1100 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 60 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 80 |

Light Source

| | |
|--------|--|
| 791831 |  An icon of a standard E27 screw-in light bulb, with the letter 'E' inside a yellow arrow pointing to the right, and the letters 'A' and 'G' stacked vertically to the left of the arrow. |
|--------|--|

Accessories

| | |
|---------|-------------------------------|
| 1006167 | NUMINOS® S , white front ring |
|---------|-------------------------------|