




## NUMINOS® PD PHASE S

Indoor LED recessed ceiling light black/black 2700K 36°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® PD PHASE S, which impresses as a pendant light with the best workmanship and lighting quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The pendant light can convince with a power consumption of 10.42 watts, luminous flux of 985 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                     |                            |
|-------------------------------------|----------------------------|
| Item no.:                           | 1004147                    |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V     |
| Secondary power / secondary voltage | 250mA                      |
| Pendant length                      | 250 cm                     |
| Height                              | 16.2 cm                    |
| Diameter                            | 6.5 cm                     |
| Net weight                          | 0.627 kg                   |
| Gross weight                        | 0.921 kg                   |
| Safety class                        | I                          |
| Assembly                            | Surface                    |
| Assembly details                    | Ceiling, Ceiling with Acc. |
| Dimmable                            | Yes                        |
| Dimming technology                  | trailing edge              |
| Wattage                             | 10.42 W                    |
| Lumen                               | 985 lm                     |
| Colour temperature                  | 2700 Kelvin                |
| Beam angle                          | 36 °                       |
| Color                               | black                      |
| CRI                                 | 90                         |
| UGR ≤                               | 16                         |
| LXXBXX data                         | L80B50                     |
| BIG WHITE Page                      | 88                         |

## Light Source

|        |  |
|--------|--|
| 791819 |  An energy label icon consisting of a yellow arrow pointing right, with the letters 'A' and 'G' stacked vertically inside it. |
|--------|--|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|