




NUMINOS® PD PHASE S

Indoor LED recessed ceiling light black/black 3000K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. This also includes NUMINOS® PD PHASE S, which impresses as a pendant light with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The pendant light has a power consumption of 10.42 watts, a luminous flux of 1020 lumens, a colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| | |
|-------------------------------------|---------------------------|
| Item no.: | 1004154 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 250mA |
| Pendant length | 250 cm |
| Height | 16.2 cm |
| Diameter | 6.5 cm |
| Net weight | 0.695 kg |
| Gross weight | 0.923 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling,Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Wattage | 10.42 W |
| Lumen | 1020 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 24 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 13 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 88 |

Light Source

| | |
|--------|--|
| 791815 |  A small icon of a yellow E27 light bulb with the letter 'E' inside a yellow arrow pointing right, and the letters 'A' and 'G' stacked vertically to the left of the arrow. |
|--------|--|

Accessories

| | |
|---------|-------------------------------|
| 1006167 | NUMINOS® S , white front ring |
|---------|-------------------------------|