




## NUMINOS® PD PHASE S

## Indoor LED pendant light white/black 3000K 24°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® PD PHASE S pendant light, which convinces with the best workmanship and lighting quality. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 10.42 watts, luminous flux of 1020 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## **TECHNICAL DATA**

Item no.:	1004158
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	250mA
Pendant length	250 cm
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.683 kg
Gross weight	0.919 kg
Safety class	1
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	10.42 W
Lumen	1020 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR≤	13
LXXBXX data	L80B50
BIG WHITE Page	88



## Light Source

791815	E
Accessories	
1006167	NUMINOS® S , white front ring