


## 3~ NUMINOS® PHASE M

## 3 phase system light black/black 2700K $24^{\circ}$

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The diverse downlights and spotlights make a thousand lighting design options possible. Like with the 3~ NUMINOS® PHASE M 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1925 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMI-NOS ® from SLV?



## **TECHNICAL DATA**

Item no.:	1004170
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.77 kg
Gross weight	1.06 kg
Safety class	I
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	1925 lm
Colour temperature	2700 Kelvin
Beam angle	24 °
Color	black
CRI	90
UGR≤	16
LXXBXX data	L80B50
BIG WHITE Page	64



## **Light Source**

791800	A E
Accessories	
1006168	NUMINOS® M , white front ring