




## 3~ NUMINOS® PHASE M

3 phase system light whitek/black 2700K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the 3~ NUMINOS® PHASE M 3-phase system light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1925 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS® from SLV?



## TECHNICAL DATA

Item no.:	1004174
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.77 kg
Gross weight	1.06 kg
Safety class	I
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	1925 lm
Colour temperature	2700 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L80B50
BIG WHITE Page	64

## Light Source

791800	 An energy label icon consisting of a yellow arrow pointing right, with the letters 'A' and 'G' stacked vertically inside it.
--------	--

## Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------