




## 3~ NUMINOS® PHASE M

3 phase system light black/black 4000K 36°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. Also with the 3~ NUMINOS® PHASE M 3-phase system light LED, which convinces with best workmanship and light quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 2120 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.:	1004187
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.77 kg
Gross weight	1.06 kg
Safety class	I
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	2120 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L80B50
BIG WHITE Page	64

## Light Source

791825	 An energy label icon consisting of a yellow arrow pointing right, with the letters 'A' and 'G' stacked vertically inside it.
--------	--

## Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------