




NUMINOS® CL PHASE M

Indoor LED surface ceiling light black/black 3000K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® CL PHASE M indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1970 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.:	1004227
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.83 kg
Gross weight	1.13 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	1970 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR ≤	13
LXXBXX data	L80B50
BIG WHITE Page	82

Light Source

791822	 An energy label icon consisting of a yellow arrow pointing right, with the letters 'A' and 'G' stacked vertically inside it.
--------	--

Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------