




NUMINOS® CL PHASE M

Indoor LED surface ceiling light white/black 3000K 36°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® CL PHASE M indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1970 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1004231 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500mA |
| Height | 18.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.68 kg |
| Gross weight | 0.93 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Wattage | 20.1 W |
| Lumen | 1970 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 36 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 13 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 82 |

Light Source

| | |
|--------|---|
| 791822 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006168 | NUMINOS® M , white front ring |
|---------|-------------------------------|