


## NUMINOS® CL PHASE M

## Indoor LED surface ceiling light white/black 4000K 60°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® CL PHASE M indoor ceiling-mounted light LED, which impresses with its high-quality work-manship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 2060 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



## **TECHNICAL DATA**

Item no.:	1004240
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	500mA
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.68 kg
Gross weight	0.93 kg
Safety class	1
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	2060 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR≤	25
LXXBXX data	L80B50
BIG WHITE Page	82



## Light Source

791825	E
Accessories	
1006168	NUMINOS® M , white front ring