




NUMINOS® PD PHASE M

Indoor LED recessed ceiling light black/black 3000K 24°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® PD PHASE M pendant light, which convinces with the best workmanship and lighting quality. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The pendant light has a power consumption of 20.1 watts, a luminous flux of 1955 lumens, a colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|-------------------------------------|----------------------------|
| Item no.: | 1004250 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500mA |
| Pendant length | 250 cm |
| Height | 18.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.953 kg |
| Gross weight | 1.201 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling, Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Wattage | 20.1 W |
| Lumen | 1955 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 24 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 16 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 90 |

Light Source

| | |
|--------|--|
| 791822 |  An energy label icon consisting of a yellow arrow pointing right, with the letters 'A' and 'G' stacked vertically inside it. |
|--------|--|

Accessories

| | |
|---------|-------------------------------|
| 1006168 | NUMINOS® M , white front ring |
|---------|-------------------------------|