




NUMINOS® PD PHASE M

Indoor LED recessed ceiling light black/black 4000K 36°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® PD PHASE M pendant light, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 2120 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| Item no.: | 1004259 |
|--|---------------------------|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary volta- ge | 500mA |
| Pendant length | 250 cm |
| Height | 18.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.955 kg |
| Gross weight | 1.201 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling,Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Wattage | 20.1 W |
| Lumen | 2120 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 36 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 16 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 90 |
| | , |



Light Source

| 791825 | A E |
|-------------|-------------------------------|
| Accessories | |
| 1006168 | NUMINOS® M , white front ring |