




## 3~ NUMINOS® PHASE L

3 phase system light white/black 3000K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. The different downlights and spotlights make a thousand lighting design options possible. Also with the 3~ NUMINOS® PHASE L 3-phase system light LED, which convinces with best workmanship and light quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2430 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



## TECHNICAL DATA

Item no.:	1004278
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700mA
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.07 kg
Gross weight	1.4 kg
Safety class	I
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	28 W
Lumen	2430 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR ≤	13
LXXBXX data	L80B50
BIG WHITE Page	66

## Light Source

791822	 The logo consists of the letters 'A' and 'G' stacked vertically in a small square, followed by a yellow arrow pointing to the right containing the letter 'E'.
--------	--

## Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------