




## 3~ NUMINOS® PHASE L

3 phase system light white/black 4000K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the 3~ NUMINOS® PHASE L 3-phase system light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2715 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1004288                |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700mA                  |
| Length                              | 21.3 cm                |
| Height                              | 18 cm                  |
| Diameter                            | 10 cm                  |
| Net weight                          | 1.07 kg                |
| Gross weight                        | 1.4 kg                 |
| Safety class                        | I                      |
| Assembly details                    | Track Ceiling          |
| Dimmable                            | Yes                    |
| Dimming technology                  | trailing edge          |
| Wattage                             | 28 W                   |
| Lumen                               | 2715 lm                |
| Colour temperature                  | 4000 Kelvin            |
| Beam angle                          | 60 °                   |
| Color                               | white                  |
| CRI                                 | 90                     |
| UGR ≤                               | 22                     |
| LXXBXX data                         | L80B50                 |
| BIG WHITE Page                      | 66                     |

## Light Source

|        |  |
|--------|--|
| 791825 |  |
|--------|--|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|