




## **NUMINOS® CL PHASE L**

## Indoor LED surface ceiling light black/black 2700K $24^{\circ}$

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® CL PHASE L indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2440 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## **TECHNICAL DATA**

Item no.:	1004314
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	700mA
Height	21.3 cm
Diameter	10 cm
Net weight	0.95 kg
Gross weight	1.26 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	28 W
Lumen	2440 lm
Colour temperature	2700 Kelvin
Beam angle	24°
Color	black
CRI	90
UGR≤	19
LXXBXX data	L80B50
BIG WHITE Page	84



## **Light Source**

791800	E
Accessories	
1006169	NUMINOS® L , white front ring